

imageRUNNER ADVANCE DX 6780i/6765i 6755i

imageRUNNER ADVANCE DX 6700 Series

Print up to 80 ppm (BW)

Scan up to 270/270 ipm (300 dpi) (BW/color, duplex)

Print up to 11" × 17"

8,020-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.





### WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.<sup>1</sup>
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder, and automatically print with predefined settings such as number of copies and finishing requirements.



## **SECURITY**

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM\*.<sup>2</sup> systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control<sup>3</sup> utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>4</sup>



# QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

<sup>\*</sup> Security Information and Event Management



## DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



## COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.

## **CONFIGURATION OPTIONS**



#### STAPLE FINISHER-AC1

- 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Supports Staple-free\* Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)




#### **BOOKLET FINISHER-AC1**

- · 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



#### DOCUMENT INSERTION/ FOLDING UNIT-J1

- Insert pre-printed sheets
- Up to 11" × 17"
- 1-tray, 100-sheet capacity
- Z-fold, C-fold



#### DOCUMENT INSERTION UNIT-P1

- Insert pre-printed sheets
- Up to 11" × 17"
- 1-tray, 100-sheet capacity



#### imagePASS-Y3 v1.1

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules



**UTILITY TRAY-B1** 

UPRIGHT CONTROL PANEL-J1

- 3,660-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports up to 11" x 17"
- User adjustable



#### PAPER DECK UNIT-E1

- 3,660-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports LTR

#### **SPECIFICATIONS**

#### Main Unit

Type

Monochrome Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send, Store

Optional: Fax

Processor

1.75GHz Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Color Flat Touch-panel Standard: Optional 10.4" TFT LCD SVGA Color Upright Touch-panel

Memory 3.0 GB RAM

Hard Disk Drive 250 GB Standard: Maximum: 1TB

Interface Connection

Network

1000Base-T/100Base-TX/10Base-T Standard: Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy

Others

Standard USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

Optional: Copy Control Interface Paper Capacity (LTR, 20 lb, Bond)

4.360 Sheets Standard: Maximum: 8.020 Sheets Paper Sources (LTR, 20 lb. Bond)

Dual 1,560-sheet Paper Drawers, Dual Standard:

570-sheet Paper Cassettes, 100-sheet Multipurpose Tray

3,660-sheet Paper Deck Optional:

(Paper Deck Unit-E1 or POD Deck Lite-C1)

Paper Output Capacity (LTR, 20 lb. Bond)

With Copy Tray: 250 Sheets

With External 3,500 Sheets (with Staple Finisher-AC1 or

Booklet Finisher-AC1) Finishers:

Finishing Capabilities

With External Collate, Group, Offset, Staple, Saddle-Stitch, Hole Punch, Eco Staple, Finishers:

Staple On Demand, Document Insertion,

Z-fold, C-fold Supported Media Types

Paper Cassettes: Thin, Plain, Recycled, Color, Heavy, Bond,

Pre-punched, Letterhead, Tab<sup>5</sup>

Thin, Plain, Recycled, Color, Heavy, Tracing,6 Multipurpose Bond, Transparency, Label, Pre-punched, Tray:

Letterhead, Tab

Paper Decks: Thin, Plain, Recycled, Color, Heavy,

Pre-punched, Letterhead, Bond, Transparency, Labels, Tab

Supported Media Sizes

Multipurpose 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size/Free Size (4" x 5-7/8" to 11-3/4" x 19-1/4") Tray:

Paper Decks: Letter

Paper Cassettes: 11"x17", Legal, Letter, Letter-R, Executive, Statement-R, Custom size (5-1/2" x 7-1/8" to

11-3/4" x 19-1/4")

Supported Media Weights

Paper Decks: 14 lb. Bond to 80 lb. Cover (52 to 220 g/ $m^2$ ) Paper Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²) Multipurpose Tray: 14 lb. Bond to 140 lb. Index (52 to 256 g/m²) Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

Print/Copy Speed

Up to 80 ppm (Letter) 6780i: Up to 61 ppm (Letter-R)

Up to 48 ppm (Legal) Up to 40 ppm (11" x 17") Up to 65 ppm (Letter)

Up to 50 ppm (Letter-R) Up to 39 ppm (Legal) Up to 32 ppm (11" x 17") Up to 55 ppm (Letter)

Up to 43 ppm (Letter-R) Up to 39 ppm (Legal) Up to 32 ppm (11" x 17")

Warm-up Time

Approx. 30 Seconds<sup>7</sup> From Power On: Approx. 30 Seconds8 From Sleep

Mode:

Quick Startup Approx. 4 Seconds9

Mode:

Basic:

Fully

6765i:

6755i:

Dimensions (W x D x H)

26-3/8" x 30-3/8" x 46-5/8" (670 x 770 x 1,185 mm)

Installation Space (W x D)

60-3/8" x 53-1/4" (1,533 mm x 1,353 mm)

(with Multi-purpose Tray/upper-right cover open + front cover open + Copy Tray) 95-7/8" x 53-1/4" (2,436 mm x 1,353 mm) (with POD Deck Lite-C1 + Document

Configured: Insertion/Folding Unit-J1 + Booklet Finisher-AC1/Staple Finisher-AC1 + Main unit front

cover open )

Weight

Approx. 491.6 lb (223 kg)10

**Print Specifications** 

Print Resolution (dpi)

1200 x 1200

Standard Page Description Languages

UFR II, PCL® 6, Adobe® PS® 3

Supported File Types

PDF, TIFF, JPEG, EPS," XPS

Printing from Mobile and Cloud

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Google Cloud Print, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for

further information.

Fonts

PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),12

Barcode Fonts<sup>13</sup>

DS. 136 Roman

Operating System<sup>14</sup>

UFRII/PS: Windows® 7/8.1/10/Server 2008/Server

2008 R2/Server 2012/Server 2012 R2/ Server 2016/Server 2019, MAC OS X

(10.10 or later)

Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/

Server 2016/Server 2019

Windows® 7/8.1/10, MAC OS X (10.9 or later) PPD:

Copy Specifications

First-Copy-Out Time (Letter)

6780i: As fast as 3.1 seconds 6765i/6755i: As fast as 3.3 seconds

Copy Resolution (dpi)

600 x 600

Multiple Copies

Up to 9,999 Copies

Magnification

25%-400% (1% Increments)

Preset Reductions/Enlargements

25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%, 400%

Scan Specifications

Single-pass Duplexing Automatic Document Feeder

**Document Feeder Paper Capacity** 

Up to 200 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R,

Custom size: 2-3/4" x 5-1/2" to 12" x 17"

Document Feeder Supported Media Weights

Single-sided/Double-sided scanning 13.3 lb Bond to 80 lb. Cover (50 to 220 gsm)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects

Max. Platen

Scanning Size: Up to 11-3/4" x 17" (297 mm x 431.8 mm)

Pull Scan

Color Network ScanGear2 for both Twain and WIA

Supported OS: Windows 7/8.1/10

Server 2008/Server 2008 R2/Server 2012/

Server 2012 R2/Server 2016

Scan Resolution (dpi)

600 x 600 Scan for Copy:

(Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), Scan for Send:

(Pull) 600 x 600

Scan for Fax:  $600 \times 600$ 

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (Letter)

Single-sided Scanning

BW/Color: 135 (300 dpi)/80 (600 dpi)

Double-sided Scanning

BW/Color: 270 (300 dpi)/160 (600 dpi)

**Send Specifications** 

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box,

Super G3 Fax (Optional), IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Up to 600 x 600 Push: Up to 600 x 600 Pull:

Communication Protocol FTP, SMB v3.0, WebDAV File:

SMTP, POP3 Email:

File Format

TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

(Optional)

Modem Speed

Super G3: 33.6 Kbps 14.4 Kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dni)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size Statement-R to 11" x 17

Fax Memory

Up to 30,000 Pages (2,000 jobs)

Speed Dials Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup

**Store Specifications** 

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 30,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV Windows (Windows 8.1/10) Supported

Client PC: Concurrent Connections (Max.): SMR-

WebDAV: 3 (Active Sessions) Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD); 480 GB (With Optional 1 TB HDD) Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW

Online Express, 15 User Authentication, Department ID Authentication, (Device and Function Level Log-in), Access

Management System

Optional: uniFLŎW

Data

Standard: Trusted Platform Module (TPM),

Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated), Verify System at Startup,3

McAfee Embedded Control<sup>3</sup>

Hard Disk Drive Mirroring, IEEE 2600.2 Optional: Common Criteria Certification, Data Loss

Prevention (Requires uniFLOW)

Network

Encrypted Secure Print, IP/Mac Standard:

Address Filtering, IPsec, TLS Encrypted Communication (v1.0/1.1/1.2/1.3), SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermark, Secure Print, Adobe

LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature,

User Signature

**Environmental Specifications** 

**Operating Environment** 

Temperature: 50 to 86 °F

20 to 80 % RH (Relative Humidity) Humidity:

Power Requirements 110-127 V AC, 60 Hz, 16 A

**Power Consumption** 

Maximum: Approx. 2,032 W Approx. 278 W<sup>16</sup> Standby:

Sleep Mode: 0.9 W17

Typical Electricity Consumption (TEC) Rating<sup>18</sup>

6780i: 1.65 kWh

Standards

ENERGY STAR Certified: 6780i Rated EPEAT Gold: 6780i

Consumables

Toner

GPR-38 Black Toner

Toner Yield (Estimated @ 6% Coverage)

56,000 Pages

- Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.
- Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
- This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on. Requires additional option.

Tab Feeding Attachment-B1 is required.

- <sup>6</sup> Some types of tracing paper cannot be used.
- Time from device power-on until copy ready (not print reservation).
- <sup>8</sup> Time from exiting Sleep mode to when printing is operational.
- <sup>9</sup> Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display.
- Including ADF, optional Upright Touch Panel and the toner bottle.
- EPS can be printed directly only from the Remote User
- Interface.
  Requires the optional PCL International Font Set-Al.
- Requires the optional Barcode Printer Kit-D1.
- Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix, may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- No charge for this solution; however, activation is required.
- Standby Reference Value: measured one unit.

  O.9 W Sleep mode not available in all circumstances due to certain settings.
  Based on ENERGY STAR Product Specification for Imaging



**f** 🔰 (0) 🔼 in



